



Ratings Range

400/230 V - 50 Hz

Standby	kW	176
	kVA	220
Prime	kW	160
	kVA	200



Benefits and features

Rehiko premium quality

- Design offices using the latest technical innovations
- Modern fully certified factories
- A cutting edge laboratory
- The generating set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested
- Approved for use with HVO (Hydrotreated Vegetable Oil) according to EN15940

Rehiko premium performances

- Optimized and certified sound levels
- Reliable power, even in extreme conditions
- Optimized fuel consumption
- Compact footprint
- Best quality of electricity, high starting and loading capacity, according to ISO8528-5
- Robust base frames and high-quality enclosures
- Protection of installations and people
- Approved in line with the most stringent standards

Engines

- Rehiko Premium level engines
- High power density, small footprint
- Low temperature starting capability
- Long maintenance interval

Alternator

- Provide industry leading motor starting capability
- Built with a class H insulation and IP23

Cooling

- A compact and complete solution using a mechanically driven radiator fan
- Designed or optimized by Rehiko
- High temperature and altitude product capacity available

Base frame and enclosure

- High quality steel with enhanced corrosion resistance
- Highly durable QUALICOAT-certified epoxy paint
- Minimum 1500 hours of resistance to salt spray in accordance with ISO12944
- Ergonomic access to allow easy maintenance and connection of the generator
- Robust design optimized for transportation

Generator sets ratings

General Specifications

Manufacturer

Rehiko

Engine ref.

KD83L06T-AA56A

Alternator choices

KH01681T

Performance class

G3

Voltage (V)

400/230

230 TRI

380/220

240 TRI

415/240

Controllers

APM303 APM403

Consumption @ 100% load ESP (L/h)*

49

Consumption @ 100% load PRP (L/h)*

44

Emission level

Not certified

Type of Cooling

Radiator

Factory installed enclosures

M149

M149-DW

M149-DW48

** Volumetric Fuel consumption is up to 4% higher when using HVO than Diesel Fuel"

		Standby rating			Prime rating	
	Hz	kWe	kVA	Amps	kWe	kVA
400/230	50	176	220	318	160	200
230 TRI	50	176	220	552	160	200
380/220	50	169	211	321	154	192
240 TRI	50	176	220	529	160	200
415/240	50	176	220	306	160	200

Engine Specifications

Engine brand	REHLKO
Engine ref.	KD83L06T-AA56A*
Air inlet system	Turbo
Cylinder configuration	6 - L
Displacement (l)	8,27
Bore (mm) x Stroke (mm)	114 x 135
Compression ratio	16.7:1
Speed 50Hz (RPM)	1500
Maximum stand-by power at rated RPM (kW)	203
Governor type	Electronic
Frequency regulation, steady state (%)	+/- 0.5%

Lubrication System

Oil Filter Quantity and type****	Spin On / 1
Charge Air coolant	Air/Air

****Rehiko recommends the use of genuine oil and filters.

Fuel System

Maximum fuel pump flow (l/h)	83
Fuel filter: Qty, type	1 / 1
	Primary Engine Filter / Fuel Water Separator
Fuel	Diesel Fuel

* Engine reference may be partially modified depending on genset application, options selected by the customer and lead time required.

Consumption with cooling system

Fuel consumption @ ESP Max Power (l/h)	49,9
Fuel consumption @ PRP Max Power (l/h)	45
Fuel consumption @ 75% of PRP Power (l/h)	32,5
Fuel consumption @ 50% of PRP Power (l/h)	22,1

Cooling system

Ambient temperature design (°C)	40
Radiator & Engine capacity (l)	30,8
Fan power 50Hz (kW)	8,26
Fan air flow w/o restriction (m3/s)	2,5
Available restriction on air flow (mm H2O)	15
Type of coolant	Glycol-Ethylene
Radiated heat to ambient (kW)	26
Heat rejection to coolant HT (kW)	95

Coolant capacity HT, engine only (l)	12,3
Outlet coolant temperature (°C)	
Max coolant temperature, Shutdown (°C)	104
Thermostat begin of opening HT (°C)	82
Thermostat end of opening HT (°C)	95

Cooling system

Radiator & Engine capacity (l)	30,8
Fan power 50Hz (kW)	8,26
Fan air flow w/o restriction (m3/s)	2,5
Available restriction on air flow (mm H2O)	15
Type of coolant	Glycol-Ethylene
Radiated heat to ambient (kW)	26
Heat rejection to coolant HT (kW)	95
Coolant capacity HT, engine only (l)	12,3
Max coolant temperature, Shutdown (°C)	104
Thermostat begin of opening HT (°C)	82
Thermostat end of opening HT (°C)	95

Exhaust system

Exhaust gas temperature @ ESP (°C)	587
Exhaust gas flow @ ESP (l/s)	592

Electrical system

Battery voltage (V)	12
---------------------	----

Air Intake system

Combustion air flow (l/s)	210
Radiated heat to ambient (kW)	26

Alternator Specifications

Number of pole	4
Technology	Brushless
AVR Regulation	Yes
Insulation class	H
Indication of protection	IP23
Number of bearing	1
Number of wires	06
Coupling	Direct
Overspeed (rpm)	2250
Voltage regulation at established rating (+/- %)	0,5
Unbalanced load acceptance ratio (%)	8

Alternator standard features

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Superior voltage waveform

Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.




APM303 controller

The APM303 is a versatile unit which can be operated in manual or automatic mode. It offers the following features:

- Measurements: phase-to-neutral and phase-to-phase voltages, fuel level (In option : active power currents, effective power, power factors, Kw/h energy meter, oil pressure and coolant temperature levels)
- Supervision: Modbus RTU communication on RS485
- Reports: (In option : 2 configurable reports)
- Safety features: Overspeed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency (Maximum active power P<66kVA)
- Traceability: Stack of 12 stored events

For further information, please refer to the data sheet for the APM303



APM403 controller

The APM403 is a versatile control unit which allows operation in manual or automatic mode

- Measurements : voltage and current
- kW/kWh/kVA power meters
- Standard specifications: Voltmeter, Frequency meter.
- Optional : Battery ammeter.
- J1939 CAN ECU engine control
- Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
- Engine parameters: Fuel level, hour counter, battery voltage.
- Optional (standard at 24V): Oil pressure, water temperature.
- Event log/ Management of the last 300 genset events.
- Mains and genset protection
- Clock management
- USB connections, USB Host and PC,
- Communications : RS485 INTERFACE
- ModBUS protocol /SNMP
- Optional : Ethernet, GPRS, remote control, 3G, 4G
- Websupervisor, SMS, E-mails

Codes and Standards

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:

- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive 2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

Power ratings definition according to ISO8528-1 (2018-02 edition) and ISO-3046-1

Emergency Standby Power (ESP): The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <70%.

Prime Power (PRP): At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <70%.

Warranty informations

Standard warranty period:

- for Products in "back-up" service
 - 36 months from the date the Product leaves the plant
 - 24 months from the Product's commissioning date
 - 1,000 running hours

The warranty expires when one of the above conditions is met.

- for Products in "prime" or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
 - 18 months from the date the Product leaves the plant
 - 12 months from the Product's commissioning date
 - 2,500 running hours

The warranty expires when one of the above conditions is met.

For more details regarding conditions of application and scope of the warranty please refer to our General "terms & conditions of sales".

Standard scope of supply:

All our open gensets are fitted with:

- Industrial water-cooled DIESEL engine
- Engine electronic governor
- Electric starter & charge alternator
- Battery⁽¹⁾
- Standard air filter
- Electric circuit breaker, adapted to the short-circuit current of the generating set
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with 85% vibration attenuation mounts
- frame height optimized to allow it to be moved safely by forklift
- enclosure made of new high-quality European steel with enhanced corrosion resistance
- enclosures and base frames tested and analyzed by the French Corrosion Institut
- 100% of tanks tested for permeability
- Personal protection ensured by protective grilles on hot and rotating parts
- Separate 9 dB(A) silencer
- Fuel tank welded inside the genset frame
- Retention bund included for gensets up to 250 kVA ESP
- Emergency stop button on the outside
- Flexible fuel lines & lub oil drain cock
- Oil⁽²⁾ and antifreeze liquid⁽²⁾
- Exhaust outlet with flexible and flanges
- User's manual (1 copy)
- Packing under plastic film

⁽¹⁾ excluded from the supply up to 165 kVA ESP if assembled outside Europe

⁽²⁾ excluded from the supply up to 830 kVA ESP if assembled outside Europe

Dimensions and Weights

Compact version

Overall Size, max., L x W x H, (mm)	2497 x 1103 x 1644
Dry weight (kg)	1760
Tank capacity (L)	344



M149 - Dimensions soundproofed version

Overall Size, max., L x W x H, (mm)	3590 x 1147 x 1899
Tank capacity (L)	344
Dry weight (kg)	2320
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	96
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	80
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	70



Dimensions DW compact version

Overall Size, max., L x W x H, (mm)	2497 x 1103 x 1919
Tank capacity (L)	988
Dry weight (kg)	2020

M149 - Dimensions DW soundproofed version

Overall Size, max., L x W x H, (mm)	3590 x 1147 x 2174
Tank capacity (L)	988
Dry weight (kg)	2570
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	96
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	80
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	70



Dimensions DW 48h compact version

Overall Size, max., L x W x H, (mm)	3563 x 1103 x 2079
Tank capacity (L)	1935
Dry weight (kg)	2270

M149 - Dimensions DW 48h soundproofed version

Overall Size, max., L x W x H, (mm)	3590 x 1147 x 2334
Tank capacity (L)	1935
Dry weight (kg)	2850
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	96
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	80
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	70



** dimensions and weight without options*

Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L.
Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.